

SYMBOL

MODEL NO.	BODY DASH No. (ITEM 1)	PORT "G"	PORT "3"	TH'D TYPE
H2Q	-001	.250-18 NPTF	SAE-6	INCH
H2Q/M	-002	.250-19 BSPP	.250-19 BSPP	METRIC

REVISION

PART NO.

H2Q

MOUNTING HOLES:
INCH : .375-16 UNC x .62 DP.
METRIC : M10 x 1.5-6H x .62 DP.
TYP (2) PLACES

T-17A CAVITY
L.S. DEPTH = 1.44

PORT "3"
PER CHART

PORT "G"
PER CHART

NOTES:

1. SEALS: BUNA-N

2. ALUMINUM BODIES-3000
PSI MAXIMUM CONTINUOUS
SERVICE PRESSURE.

3. CXGD XCN CARTRIDGE:
CRACKING PRESSURE: 30 PSI ±3
CHECK SEAT: STEEL

4. ORDERING INFO:
PBHB LAN H2Q

1.25 DIA SAE CODE 61
4 BOLT FLANGE PATTERN
TYP (2) PLACES
INCH: .438-14 UNC x 1.12 DP.
METRIC : M10 x 1.5-6H x 1.12 DP.
TYP (8) PLACES

MAIN PORT DESIGNATION

CART. TO BE INSTALLED IN T-17A
CAVITY. SEAL TYPE IN PBHB
DETERMINES ITEM 2 SEAL TYPE

LET	REVISION	DATE	DRN	CHK	REL

OUTLINE & ASSEMBLY

TITLE

PRESS. REDUCING VALVE
WITH REVERSE FREE FLOW

SCALE

REF.

1/2 YPGA LAN

MATERIAL

ALUM & STEEL

HEAT TREAT & FINISH

DRWN

DEA

DATE

11-22-91

CHECK

DATE

RELEASE

3399

DATE

11-27-91

ITEM

2

CXGD XCN

CHECK VALVE

1

ITEM

1

150-753-SEE CHART

BODY

1

ITEM

PART NO.

PART NAME

QTY

REVISION

PART NO.

H2Q

SUN hydraulics®

1500 UNIVERSITY PARKWAY
SARASOTA, FLORIDA 34243, US
TELEPHONE (813) 355-2983