
CHART A (PORT OPTIONS)				
MODEL NUMBER	PORT G	PORTS 1 & 2	PORT 3	BODY DASH NO ITEM 1
H4D	.250-18 NPTF	.750-14 NPTF	.750-14 NPTF	-001
H4E	.250-18 NPTF	1.00-11.5 NPTF	.750-14 NPTF	-002
H4F	.250-18 NPTF	1.25-11.5 NPTF	.750-14 NPTF	-003
H4L	.250-18 NPTF	SAE-12	SAE-12	-004
H4M	.250-18 NPTF	SAE-16	SAE-12	-005
H4N	.250-18 NPTF	SAE-20	SAE-12	-006
H4W	.250-19 BSPP	.750-14 BSPP	.750-14 BSPP	-007
H4X	.250-19 BSPP	1.00-11 BSPP	.750-14 BSPP	-008
H4Y	.250-19 BSPP	1.25-11 BSPP	.750-14 BSPP	-009

REVISION	PART NO.
A	H4*

SYMBOL



NOTES:

1. SEALS: BUNA-N
2. ALUMINUM BODIES-3000 PSI MAXIMUM CONTINUOUS SERVICE PRESSURE.
3. CXGD XCN CARTRIDGE: CRACKING PRESSURE: 30 PSI ±3 CHECK SEAT: STEEL
4. ORDERING INFO:
   PBHB LAN H4*
   - H4* — MAIN PORT DESIGNATION
   - PBHB — CART. TO BE INSTALLED IN T-17A CAVITIES. SEAL TYPE IN PBHB DETERMINES ITEM 2 SEAL TYPE

ITEM	PART NO.	PART NAME	QTY
2	CXGD XCN	CHECK VALVE	1
1	150-754-SEE TABLE	BODY	1

OUTLINE & ASSEMBLY

LET	REVISION	DATE	DRN	CHK	REL
A	PORT #3 ON -009 WAS .250-19 BSPP	22 NOV94	BRS		6167

UNLESS OTHERWISE SPECIFIED
DIMENSION TOL
.x ±.030
.xx ±.015
.xxx ±.005
ANGLE TOL ±½
FINISH 80√
REMOVE ALL BURRS

TITLE T-17A CAVITY WITH REVERSE FREE FLOW

SCALE	REF.	MATERIAL
1/2	YPGC LAN	ALUM & STEEL

DRAWN	CHECK	RELEASE	HEAT TREAT & FINISH
BRS	R/B	2886	
DATE 10-23-90	DATE 11-12-90	DATE 11-18-90	

REVISION	PART NO.
A	H4*

sun hydraulics® CORPORATION
1500 UNIVERSITY PARKWAY
SARASOTA, FLORIDA 34243, US
TELEPHONE (813) 355-2983