


SYMBOL



1 2

NOTES :

1)SEALS= BUNA N.

2)ALUMINUM BODIES-3000
PSI MAXIMUM CONTINUOUS
SERVICE PRESSURE.

3)FOR OTHER OPTIONS SEE
OPTION SHEET.

-.41 DIA THRU
CBORED .500 DIA
x .31 DP
TYP (6) PLACES.

Technical drawing of a rectangular plate with two circular features labeled 1 and 2. The drawing includes dimensions for radii, diameters, and distances between features. Feature 1 is a larger circle with concentric circles inside, and Feature 2 is a smaller circle with concentric circles inside. The plate has a rectangular border with rounded corners. Dimensions are given in millimeters.

Dimensions:

- Overall width: 2.50
- Overall height: 4.00
- Distance from left edge to center of Feature 1: 1.25
- Distance from right edge to center of Feature 1: 1.25
- Distance from left edge to center of Feature 2: 0.31
- Distance from right edge to center of Feature 2: 2.19
- Distance from top edge to center of Feature 1: 3.08
- Distance from bottom edge to center of Feature 2: 0.48
- Distance from top edge to center of Feature 2: 1.36
- Distance from bottom edge to center of Feature 1: 2.65
- Radius of Feature 1: 1.00
- Radius of Feature 2: 0.92
- Radius of inner circle of Feature 1: 0.52
- Radius of inner circle of Feature 2: 0.48


sunhydraulics
GARCOTA, FL. USA
V7H


2.50

T-10A CAVITY
.07 L.S. DEPTH
TYP BOTH ENDS—

2	500-001-214	O RING	2
1	152-568-006	BODY	1
ITEM	PART NO.	PART NAME	QTY

OUTLINE & ASSEM.

					UNLESS OTHERWISE SPECIFIED	TITLE BODY-CROSS PORT RELIEF CHARLYN 4000/6000 T-10A CAVITIES 1.00 BSPP			REVISION	PART NO.
										VZH
						DIMENSION TOL	SCALE	REF.	MATERIAL	
						.X = ±.030	1	1	ALUMINUM	
						.XX = ±.015				
					.XXX = ±.005	DRAWN	CHECK	RELEASE	HEAT TREAT & FINISH	
					ANGLE TOL ±%	<u>R/B</u>	<u>DAS</u>	<u>2870</u>		
					FINISH 80✓	DATE	DATE	DATE		
					REMOVE ALL BURRS	1-8-91	1-9-91	1-10-91		
LET	REVISION				DATE	DRN	CHK	REL		



SUN hydraulics[®]
CORPORATION
1500 UNIVERSITY PARKWAY
SARASOTA, FLORIDA 34243, US
TELEPHONE (813) 355-2983

