

1) ALUMINUM BODIES-3000 PSI
MAXIMUM CONTINUOUS SERVICE
PRESSURE.
2) FOR OTHER OPTIONS SEE OPTION
SHEET.

REVISION	PART NO.	WSY
----------	----------	-----

MOUNTING PROVISIONS
 .375-16UNC x .62 DP.
 TYP (2) PLACES

-1.25-11.5 NPTF PORT
TYP (3) PLACES


T-17A CAVITY—
1.09 DEEP L.S.

-.250-18 NPTF PORT

sunhydraulics®
SARASOTA, FL. USA
WSY

— .250-18 NPTF
GAGE PORT

SYMBOL



LET	REVISION	DATE	DRN	CHK

UNLESS OTHERWISE SPECIFIED

DIMENSION TOL
.x = ±.030
.xx = ±.015
.xxx = ±.005
ANGLE TOL ±½
FINISH 80✓
REMOVE ALL
BURRS

OUTLINE & ASSEMBLY

TITLE	TEE MTD T-17A CAVITY #2 PORT THRU
-------	--------------------------------------

SCALE	REF.
1 / 1	HI
DRAWN <i>BRS</i>	CH
DATE 4-7-89	DA

REF.	HI - CAP
CHECK	<u>R/B</u>
DATE	4-8-89

	D = WTH
	RELEASE
	DATE

	MATERIAL
	ALUMIN
E	HEAT TREAT
	

NUM BODY
AT & FINISH

REVISION	PART NO.	WSY
----------	----------	-----

