




REFER TO SUN HYDRAULICS
TECHNICAL LITERATURE AND CATALOGUE
FOR DETAILS OF CARTRIDGE STANDARD
SETTINGS, ADJUSTMENT RANGES,
MAXIMUM PRESSURE RATINGS,
SEAL MATERIAL, TORQUE VALUES, ETC.



A	ADDED CAVITY DIMENSIONS. REVISED VIEW ORIENTATION. Pr No STAMPING WAS ON OPPOSITE FACE. ADDED A P T B STAMPING	28 JAN 02	GH		
LET	REVISION	DATE	DRN	CHK	R

UNLESS OTHERWISE SPECIFIED	TITLE ISO 9000	
DIMENSION TOL (INCHES)	T-10	
.x ± .030	CADD SCALE	REF.
.xx ± .015	1:*	SEE ALSO
.xxx ± .005	DRAWN	CHECK
ANGLE TOL ± 1/2°	GH	GH
FINISH 80 ✓	DATE	DATE
REMOVE ALL BURS	06 DEC 01	06 DEC 01

055 1/2	CADD SCALE 1:*	REF. SEE ALSO W4T	
	DRAWN GH	CHECK GH	RELEASE
	DATE 06 DEC 01	DATE 06 DEC 01	DATE

E	HEAT TREAT & FINISH
	



3	500-001-014	O-RING SEAL	5
2	A330-006-006	SAE-6 PLUG	1
1	158-782-002	BODY	1
ITEM	PART NO.	PART NAME	QTY