






T-24A CAVITY
2.00 L.S. DEPTH
TYP (2) PLACES




REVISION		PART NO.	
		XLS	
MODEL NO.	BODY DASH NO.	PORT 4A	FLANGE TH'D TYPE
XLS	-001	SAE-6	INCH
XLS/M	-002	.250-19 BSPP	METRIC


PORT 4A
PER CHART



2.00 SAE CODE-61
4 BOLT FLANGE
PATTERN (4) PLACES
INCH: .500-13UNC x
1.06 DP.
METRIC: M14 x 2.0-6H
x 1.06 DP.
TYP (16) PLACES



2.56 2B 2A 1B 1A 8.25 6.12 2.12 4.50 2.25 0



INCH: .375-16UNC x
.62 DP.
METRIC: M10 x 1.5-6H
x .62 DP.
TYP (2) PLACES

NOTES:
1) ALUMINUM BODIES-
3000 PSI MAX.
CONTINUOUS SERVICE
PRESSURE.

1	152-257-SEE CHRT	BODY	1
ITEM	PART NO.	PART NAME	QTY

REVISION				PART NO.			
				XLS			
TITLE				MATERIAL			
DUAL CROSS-PILOTED T-24A CAVITIES W/Common #4 PORT-2.00 CODE-61				ALUMINUM			
SCALE				HEAT TREAT & FINISH			
1 = 2							
DRAWN				CHECK			
BRS				2338			
DATE				DATE			
11/29/89				12-18-89			
UNLESS OTHERWISE SPECIFIED				DIMENSION TOL			
				.x = ±.030			
				.xx = ±.015			
				.xxx = ±.005			
				ANGLE TOL ± 1/2°			
				FINISH 80✓			
				REMOVE ALL BURRS			
LET	REVISION	DATE	DRN	CHK	REL		

