

B

PLEASE REFER TO SUN HYDRAULICS' TECHNICAL LITERATURE / CATALOGUE INFORMATION FOR DETAILS OF STANDARD VALVE SETTINGS, ADJUSTMENT RANGES, SEALS MATERIAL, TORQUE VALUES, MAXIMUM PRESSURE RATINGS, ETC. ETC

PORT #3 _____
TYP (2) PLACES
PER CHART

MODEL No	BODY DASH No	PORT #3	THREAD TYPE
Z9U	- 001	SAE - 6	INCH
Z9U/M	- 002	1 / 4 " BSPP	METRIC

.50 DIA SAE CODE-61
 4-BOLT FLANGE PATTERN
 TYP (2) PLACES.
 MOUNTING PROVISIONS:-
 .34 DIA HOLES THRU,
 TYP (4) PLACES

Technical drawing of a rectangular plate with a circular hole. The drawing includes the following features and dimensions:

- Dimensions:**
 - Top horizontal dimension: 2.56
 - Bottom horizontal dimension: .81
 - Right vertical dimension: 0
 - Bottom right corner dimension: 0
- Features:**
 - A circular hole with concentric circles representing the hole's profile.
 - A dashed vertical line indicating a centerline or axis of symmetry.
 - A small triangle on the right side, pointing towards the center.
 - A small triangle on the bottom right corner.
 - A small triangle on the left side, pointing towards the center.
 - A small triangle on the right side, pointing away from the center.
 - A small triangle on the bottom right corner, pointing away from the center.
 - A small triangle on the left side, pointing away from the center.
- Annotations:**
 - A circled number 1 with an arrow pointing to the top edge of the plate.

2	500-001-210	O-RING SEAL	1
1	158-645-*** (SEE CHART)	BODY	1
ITEM	PART NO.	PART NAME	QTY

T-11A
CAVITY

[illegible]

SUN hydraulics[®]
LIMITED
WHEELER ROAD, WHITLEY,
COVENTRY, CV3 4LA, ENGLAND
TELEPHONE (01203) 307696