

SYMBOL



G

SYMBOL	T-3A CAVITY	REVISION	PART NO.	ZCL
--------	-------------	----------	----------	-----

750-14 NPTF PORT
TYP (3) PLACES

.41 DIA THRU _____
C-BORED .59 DIA
.34 DP. (4) PLACES

- T-3A CAVITY
.06 L.S. DEPTH

2.44 1.69 1.19

-4.94

— 3.88

SUNHYDRAULICS
SARASOTA, FL. USA
ZCL

1.38.

1.69

1.69

1.56 O.D.
REF

1.38.

1.25

2.50

-.250-18 NPTF PORT

1.00 CODE-61
4-BOLT FLANGE
PATTERN (1) PLACE

NOTES:

1) ALUMINUM BODIES-3000 PSI
MAXIMUM CONTINUOUS SERVICE
PRESSURE.
2) FOR OTHER OPTIONS SEE OPTION
SHEET.
3) SEALS: BUNA-N

OUTLINE & ASSEMBLY

TITLE	DIRECT	SAE	1.00	CODE
61	FLANGE	MTD	T-3A	CAV.

REVISION	PART NO.	ZCL
----------	----------	-----

**UNLESS
OTHERWISE
SPECIFIED**

DIMENSION TOL
.X = ±.03
.XX = ±.01
.XXX = ±.00
ANGLE TOL ±
FINISH 80-
REMOVE AL
IN 1982

SCALE

REF.

Abstract

[illegible]

MATERIALS

AL

[illegible]

--	--

SUN hydraulics®
CORPORATION
1500 UNIVERSITY PARKWAY
SARASOTA, FLORIDA 34243, USA
TELEPHONE (813) 358-2983